China

CMC

COA

Cylinder/Tank

Co

# Industrial Grade 99.9%/ 99.99%/ 99.999% Purity Cylinder Gas Co Gas Carbon Monoxide

## **Basic Information**

Place of Origin:

- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 m3
- Price: US \$8/m3
- Packaging Details:
- Delivery Time: 15 days
- Payment Terms: L/C, T/T
- Supply Ability: 50000M3/Year



## **Product Specification**

- Product Name:
- Melting Point:
- Appearance:
- Boiling Point:
- Cylinder Pressure:
- Valve:
- Cylinder Standard:
- Transport Package:
- Specification:
- Trademark:
- Origin:
- CAS No.:
- Formula:
- EINECS:
- Constituent:



Carbon Monoxide Gas

- 12.5MPa/15MPa/20MPa
  - Qf-30A/Cga350

-205ºC

- GB/ISO/DOT Sea Transportation
- 4L 8L 40L 47L 50L
- CMC
- - Suzhou, China 10102-43-9
    - Co
    - 211-128-3
      - Industrial Pure Air



## More Images









Our Product Introduction

## **Product Description**

CO gas refers to carbon monoxide (CO), which is a colorless, odorless, and highly toxic gas. It is produced by the incomplete combustion of carbon-containing substances and poses significant health risks.

Here are some key points about carbon monoxide gas:

Sources: Carbon monoxide is generated by various combustion processes, such as the burning of fossil fuels like coal, oil, and natural gas. Common sources include vehicle exhaust, industrial emissions, residential heating systems, fireplaces, and malfunctioning or poorly maintained fuel-burning appliances.

Health Effects: Carbon monoxide is dangerous because it binds to hemoglobin in red blood cells, reducing their ability to transport oxygen. Inhalation of carbon monoxide can lead to carbon monoxide poisoning, which can cause symptoms ranging from mild to severe, including headache, dizziness, nausea, confusion, and in severe cases, loss of consciousness, organ damage, or even death.

Prevention and Safety: To prevent carbon monoxide poisoning, it is crucial to ensure proper ventilation and regular maintenance of fuel-burning devices. Install carbon monoxide detectors in living areas, especially near sleeping areas, as they can provide early warning of elevated CO levels. Never use fuel-burning equipment indoors or in enclosed spaces without adequate ventilation.

Detection: Due to its odorless and colorless nature, carbon monoxide cannot be detected by human senses alone. Carbon monoxide detectors equipped with sensors are essential for monitoring CO levels in indoor environments. These detectors emit an alarm when carbon monoxide concentrations reach dangerous levels, allowing occupants to evacuate and seek fresh air.

Emergency Response: If carbon monoxide poisoning is suspected, immediately move to a well-ventilated area with fresh air. Contact emergency services and seek medical attention promptly. Do not re-enter the affected area until it has been deemed safe by professionals.

It is crucial to raise awareness about the dangers of carbon monoxide and take preventive measures to ensure safety. Regular inspection and maintenance of fuel-burning appliances, along with the installation of carbon monoxide detectors, are important steps to mitigate the risk of exposure to this toxic gas.

#### Basic Info.

Molecular Weight	28.0101	Density	1.2504G/L
Melting Point	-205ºC	Boiling Point	-191.5ºC
Appearance	Colorless,Odorless	Un No.	1016
DOT Class	2.1&2.3	Valve	QF-30A/CGA350
Cylinder Standard	GB/ISO/DOT	Cylinder Pressure	12.5Mpa/15Mpa/20Mpa
Transport Package	40L,47L,50L etc	Specification	99.9%
Trademark	CMC	Origin	China
HS Code	2811290090	Production Capacity	10000cyl/Month

#### Specification:


CAS No.: 630-08-0 EINECS No.: 211-128-3 UN No.: UN1016 Purity: 99.9%-99.999% Dot Class: 2.1 & 2.3 Appearance: Colorless Grade Standard: Industrial Grade

#### CO - Carbon Monoxide 99.9 %

H2	≤5 ppm
02	≤50 ppm
N2	≤450 ppm
CO2	≤30 ppm
CH4	≤20 ppm
H20	≤5 ppm
Total Impurity	≤1000 ppm

#### **Detailed Photos:**









## Packaging & Shipping

Product	Carbon Monoxide		
Package Size	40Ltr Cylinder	50Ltr Cylinder	
Filling Content/Cyl	6 m3	10 m3	
QTY Loaded in 20'Container	250 Cyls	250 Cyls	
Total Volume	1500 m3	2500 m3	
Cylinder Tare Weight	50Kgs	55Kgs	
Valve	QF-30A /CGA 35		

### Company

Profile



