



China Cylinder Gas High Purity Best Price C3h8 Propane Gas

Our Product Introduction

for more products please visit us on gascylindertank.com

Basic Information

- Place of Origin: China
- Brand Name: CMC
- Certification: COA
- Model Number: C3h8
- Minimum Order Quantity: 1kg
- Price: US \$3/kg
- Packaging Details: Cylinder/Tank
- Delivery Time: 15 days
- Payment Terms: L/C, T/T
- Supply Ability: 20000 Tons/Year



Product Specification

- Product Name: Propane Gas
- Cylinder Pressure: 12.5MPa/15MPa/20MPa
- Cylinder Standard: GB/ISO/DOT
- Valve: Cga350/Bwf-1
- Melting Point: -187.6 °C
- Appearance: Colorless, Odorless
- Transport Package: 40L/47L/50L/118L/926L
- Specification: 40L/47L/50L/118L/926L
- Trademark: CMC
- Origin: China
- HS Code: 2901100000
- Supply Ability: 1, 000, 000ton/Year
- CAS No.: 74-98-6
- Formula: C3h8
- EINECS: 200-827-9



More Images



Product Description

Product Description

Propane gas (C₃H₈) is a flammable hydrocarbon gas commonly used as a fuel for heating, cooking, and various other applications. It is a byproduct of natural gas processing and petroleum refining. Here are some key points about propane gas:

Properties: Propane gas possesses several important properties:

Flammability: Propane is highly flammable and can ignite easily when exposed to an ignition source. It has a lower flammability limit (LFL) of 2.1% and an upper flammability limit (UFL) of 9.6%.

Odor: Pure propane gas is odorless. However, an odorant called ethanethiol is added to commercial propane to give it a distinct, pungent odor. This odor serves as a safety measure to detect leaks.

Density: Propane gas is heavier than air and tends to sink to low-lying areas if released. This property should be considered when handling and storing propane.

Production: Propane is a byproduct of natural gas processing and crude oil refining. It is separated from natural gas or crude oil through a process called fractionation. Propane can also be produced during the processing of other hydrocarbon gases, such as butane and ethane.

Uses: Propane gas has various applications, including:

Residential and Commercial Heating: Propane is commonly used as a fuel for space heating, water heating, and heating appliances in homes and commercial buildings. It is often stored in pressurized tanks or cylinders.

Cooking: Propane is widely used as a fuel for cooking appliances, such as stoves, ovens, and grills. It provides an efficient and controllable heat source for cooking.

Transportation: Propane can be used as an alternative fuel for vehicles. It is commonly used in propane-powered vehicles, such as forklifts, buses, and some types of cars and trucks.

Industrial Applications: Propane is utilized in various industrial processes, including metal cutting and welding, drying and curing processes, and as a fuel for industrial boilers and furnaces.

Agriculture: Propane is used in agricultural applications, such as crop drying, weed control, and heating for livestock facilities.

Safety Considerations: When handling propane gas, it is essential to follow safety guidelines:

Storage and Handling: Propane should be stored in approved containers or tanks designed for pressurized gases. Proper handling techniques, such as securing tanks and ensuring proper ventilation, should be followed.

Leak Detection: Propane has an added odorant to help detect leaks. If a distinct rotten egg smell is detected, it may indicate a propane leak. In such cases, immediate action should be taken, such as turning off the gas supply and evacuating the area.

Ventilation: Adequate ventilation is crucial when using propane indoors to prevent the accumulation of gas and ensure proper air circulation.

Fire Safety: Propane is highly flammable, and precautions should be taken to prevent ignition sources near propane storage areas or when handling the gas.

Professional Assistance: It is recommended to consult and engage qualified professionals for the installation, maintenance, and repair of propane systems and appliances.

Please note that specific regulations, guidelines, and safety requirements for propane use may vary depending on the jurisdiction and application. It is crucial to adhere to local regulations and seek expert advice when dealing with propane gas.

Basic Info

Transport Package:	40L/47L/50L/118L/926L	Melting Point	-187.6 °C
Trademark:	CMC	Boiling Point	-42.1 °C
Specification	99.50%	Production Capacity	1, 000, 000ton/Year
Cylinder Pressure	15MPa/20MPa	Valve	Cga350/Bwf-1

Specification:

Dot Class:2.2

State: Liquid

Purity: 99.5%

UN NO: UN1978

CAS NO: 74-98-6

Grade Standard: Industrial Grade

Specification	≥99.5	%
Methane (CH ₄)	≤100	ppmv
Ethane (C ₂ H ₆)	≤250	ppmv
Propylene (C ₃ H ₆)	≤1000	ppmv
Moisture (H ₂ O)	≤3	ppmv
Sulfur	≤1	ppmv
Isobutane (C ₄ H ₁₀)	≤2500	ppmv
N-butane (C ₄ H ₁₀)	≤1000	ppmv

Cylinder Specifications Contents

Cylinder Capacity	Valve	Weight
47L	CGA350	19 kgs
118L	BWF-1	45 kgs
926L	BWF-1	375 kgs
ISO TANK		10 Tons

Detailed Photo





Packaging & Shipping

- Company
- Profile

About us



Shanghai Kemike Chemical Co., Ltd is staffed by trained personnel, combine many years experience in Gas industry .We supply cylinder gas, electronic gas, etc ., and the gas holder, panel, valves and fittings and other equipment, parts and engineering services to our customers in China and worldwide; The products are involved in various industrial fields, such as semiconductor chip, solar cell, LED, TFT-LCD, optical fiber, glass, laser, medicine , etc.. Our mission is to partner with our global customers to provide support, solutions and quality products that are innovative, reliable, and safe. Our products mainly include: H₂, O₂, N₂, Ar, CO₂, propane, acetylene, helium, laser mixed gas, SiH₄, SiH₂Cl₂, SiHCl₃, SiCl₄, NH₃, CF₄, NF₃, SF₆, HCL, N₂O, doping mixed gas (TMB, PH₃, B₂H₆) and other electronic gases.

SiCl ₄	NH ₃	NH ₃	CH ₃ F	SiH ₄	Kr	H ₂ S	WF ₆	F ₆ +Cl ₂
4MS	C ₃ F ₈	C ₃ F ₈	TEOS	CH ₄	PH ₃	SF ₆	C ₂	HCl+Ne
CF ₄	C ₄ F ₈	SiH ₂						TMB+H ₂
SiF ₄	C ₃ H ₈	Cl ₂						He +As
BBr ₃	C ₃ H ₆	DCE						Ge+Se
POCl ₃	N ₂	SO ₂						D+B
BCl ₃	D ₂	CO ₂						CO+NO
SiHCl ₃	CH ₂ F ₂	HF						Ar+O ₂
TMAI	DMZn	DEZn						Xe+NO
			AsH ₃	C ₂ H ₄	C ₂ H ₂	HBr	COS	
			GeH ₄	C ₂ H ₆	B ₂ H ₆	H ₂ Se	GeCl ₄	



 **Shanghai Kemike Chemical Co.,Ltd**

 +86 18762990415

 williamchen@cmc-chemical.com

 gascylindertank.com