

China

CMC

COA

Cylinder/Tank

3000 Pcs/Month

He

# China Manufacturers High Purity 5n Cylinder Gas 99.999% Gas Helium

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 Piece
- Price: US \$300/PC
- · Packaging Details:
- Delivery Time: 15 days
- Payment Terms: L/C, T/T
- Supply Ability:



## **Product Specification**

- Product Name:
- DOT Class:

• Valve:

- Cylinder Standard:
- Appearance:
- Transport Package:
- Specification:
- Trademark:
- Origin: • HS Code:
- Supply Ability:
- CAS No.:
- Formula:
- EINECS:
- Constituent:

Qf-2/Cga580 GB/ISO/DOT Colorless, Odorless He Cylinder 4L 8L 40L 47L 50L

Helium Gas

2.3 & 5.1 & 8

- CMC China
- 2812191090 3000piece/Month
- - He 231-168-5
    - Industrial Pure Air

7440-59-7



## More Images











#### **Product Description**

### **Product Description**

Helium gas (He) is a colorless, odorless, and inert noble gas. It is the second-lightest element in the periodic table and belongs to the group of elements known as noble gases. Here are some key points about helium gas:

Chemical Composition: Helium is a chemical element with the atomic number 2, meaning it has 2 protons in its nucleus. Its atomic symbol is He. Properties: Helium possesses several important properties:

Inertness: Helium is chemically inert, meaning it does not readily react with other substances. It has a stable electron configuration, making it nontoxic and non-flammable.

Density: Helium is lighter than air and has a density that is approximately 0.14 times that of air. This property causes helium-filled objects to float or rise in air.

Low Boiling and Melting Points: Helium has a boiling point of -268.93 degrees Celsius (-452 degrees Fahrenheit) and a melting point of -272.2 degrees Celsius (-458 degrees Fahrenheit). These extremely low temperatures make helium useful in cryogenics.

Low Solubility: Helium is sparingly soluble in water and most other common solvents.

Occurrence and Production: Helium is one of the most abundant elements in the universe but is relatively rare on Earth. It is primarily produced as a byproduct of natural gas extraction. Certain natural gas deposits contain significant amounts of helium, which can be separated and purified. Uses: Helium gas has several practical applications:

Cryogenics: Helium is commonly used as a cryogenic refrigerant due to its extremely low boiling point. It is used to cool superconducting magnets in magnetic resonance imaging (MRI) machines, particle accelerators, and other scientific and medical equipment.

Balloons and Airships: Helium's low density makes it ideal for filling balloons and airships, providing buoyancy for their flight.

Welding: In certain specialized welding processes, helium is mixed with other gases to create an inert atmosphere that protects the weld from oxidation and improves heat transfer.

Leak Detection: Helium is often used as a tracer gas for leak detection in various industries. Its small atom size and inertness make it an effective indicator of leaks in systems and containers.

Breathing Mixtures: Helium-oxygen mixtures, known as heliox, are used in deep-sea diving and certain medical applications to reduce the effects of high pressure on the body.

Scientific Research: Helium is used in various scientific research applications, such as in cryogenics, spectroscopy, and as a carrier gas in gas chromatography.

Safety Considerations: Helium is generally considered safe and non-toxic when handled properly. However, as with any compressed gas, proper handling, storage, and transportation practices should be followed to ensure safety.

Helium is a fascinating element with unique properties, and its applications range from scientific research to everyday uses like filling balloons.

However, its availability is limited, and it is important to use helium responsibly to ensure its long-term availability for essential applications.

#### Basic Info.

DOT Class	2.2	Un Number	1963
Cylinder Standard	DOT/ISO/GB	Cylinder Pressure	15MPa/20MPa
Valve	Qf-2/Cga580	Melting Point	-272.2 ºC
Appearance	Colorless, Odorless	Boiling Point	-272.2 ºC
Density	0.1786 Kg/M3	Molecular Weight	4.0026
Transport Package	40L, 47L, 50L	Specification	99.999%, 99.9999%
Trademark	CMC	Origin	Suzhou,China
HS Code	28042900	Production Capacity	20, 000 Tons/Yea



#### Specification:

**Company Profile** 



