China

CMC

COA

H2s

Cylinder/Tank

## China Best Price Cylinder Gas Industrial H2s Gas Sulfide Hydrogen


#### **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1kg
- Price: US \$15/kg
- Packaging Details:
- Delivery Time: 15 days
- Payment Terms: L/C, T/T
- Supply Ability: 5000kg/month



## **Product Specification**

- Product Name:
- Melting Point:
- Appearance:
- Boiling Point:
- Cylinder Pressure:
- Valve:
- Cylinder Standard:
- Transport Package:
- Specification:
- Trademark:
- Origin:
- HS Code:
- Supply Ability:
- CAS No.:
- Formula:



Hydrogen Sulfide

-85.5 ºC

China

28309090

7783-06-4

H2s

20000tons/Year



#### More Images





### **Product Description**

Hydrogen sulfide (H2S) gas is a colorless, flammable, and highly toxic gas with a distinct odor of rotten eggs. It occurs naturally in some environments, such as swamps, volcanic gases, and certain industrial processes. Hydrogen sulfide is also produced by the breakdown of organic matter containing sulfur, such as in sewage and manure.

Here are some key points about hydrogen sulfide gas:

Toxicity: Hydrogen sulfide is highly toxic and poses significant health risks. Even low concentrations can cause irritation of the eyes, respiratory system, and mucous membranes. Higher concentrations can lead to more severe symptoms, including headaches, nausea, dizziness, unconsciousness, and even death.

Sources: Hydrogen sulfide can be released from various sources, including industrial processes like petroleum refining, natural gas extraction, and wastewater treatment. It can also be encountered during certain agricultural activities, mining operations, and in confined spaces with poor ventilation.

Detection and Monitoring: Due to its toxic nature, hydrogen sulfide should be carefully monitored in occupational and industrial settings. Gas detectors and monitors are commonly used to measure and alert workers to the presence of hydrogen sulfide in the air.

Safety Precautions: When working in environments where hydrogen sulfide may be present, appropriate safety precautions should be taken. This includes providing adequate ventilation, using personal protective equipment (such as respirators and gas detectors), implementing safety protocols, and training workers on the risks and proper response procedures.

Treatment and First Aid: In cases of hydrogen sulfide exposure, immediate medical attention is crucial. Affected individuals should be removed from the contaminated area and provided with fresh air. If necessary, cardiopulmonary resuscitation (CPR) and other life-saving measures may be required.

Due to the toxic nature of hydrogen sulfide gas, it is essential to prioritize safety and follow established guidelines and regulations when working with or around this gas.

#### Basic Info.

DOT Class	2.3 & 2.1	Un No	1053
Cylinde	DOT/ISO/GB	Cylinder Pressure	15MPa/20MPa
Valve	Cga330	Melting Point	-85.5 ºC
Appearance	Colorless, Rotten Egg Smell	Boiling Point	-60.4 ºC
Density	1.36 Kg/M3	Molecular Weight	34.08
Transport Package	47L, 800L	Specification	99.5%, 99.9%
Trademark	CMC	Origin	China
HS Code	28309090	Production Capacity	2000 Tons/Year

#### Specification:

Specification	Company Standard	
H25	≥ 98%	
H25 H2	50.08N	
CO2 N2 C3H8	\$1.6%	
N2	\$0.08%	
C3H8	S0.02%	
02	\$ 0.02%	
Moisture	\$ \$0 ppm	





# PRODUCT LINE









Profile





+86 18762990415 iliamchen@cmc-chemical.com @ gascylindertank.com