



China Cheap Electronic Grade Cylinder Gas 99.999% 5n C₂H₄ Gas Ethylene

Our Product Introduction

for more products please visit us on gascylindertank.com

Basic Information

- Place of Origin: China
- Brand Name: CMC
- Certification: COA
- Model Number: C₂H₄
- Minimum Order Quantity: 1kg
- Price: US \$2/kg
- Packaging Details: Cylinder/Tank
- Delivery Time: 15 days
- Payment Terms: L/C, T/T
- Supply Ability: 50000kg/month



Product Specification

- Product Name: Ethylene Gas
- Boiling Point: -103.9°C
- Appearance: Colorless
- Melting Point: -169.4°C
- Model No: Ethylene
- Transport Package: 40L
- Specification: 40L
- Trademark: CMC
- Origin: Suzhou, China
- HS Code: 2812190091
- Supply Ability: 5000 Tons Per Month
- CAS No.: 74-85-1
- Formula: C₂H₄
- EINECS: 200-815-3
- Constituent: Industrial Pure Air



More Images



Product Description

Product Description

Ethylene gas (C₂H₄) is a colorless, flammable gas with a slightly sweet odor. It is a naturally occurring plant hormone and is also produced industrially for various applications. Ethylene is involved in several biological and industrial processes. Here are some key points about ethylene gas:

Natural Occurrence: Ethylene is produced naturally in plants as a hormone and plays a crucial role in various physiological processes, including:

Ripening of Fruits: Ethylene is responsible for triggering the ripening process in many fruits. As fruits mature, they release ethylene, which promotes the breakdown of cell walls, softening of the fruit, and changes in color, flavor, and aroma.

Flowering and Senescence: Ethylene influences the flowering of some plants and stimulates the senescence (aging) of flowers and leaves.

Stress Responses: Plants release ethylene in response to various environmental stresses, such as drought, flooding, and mechanical damage.

Ethylene helps regulate adaptive responses to these stresses.

Industrial Applications: Ethylene gas also has several industrial applications:

Petrochemical Industry: Ethylene is a key raw material in the petrochemical industry. It is used as a feedstock for the production of numerous chemicals, including polyethylene (the most widely produced plastic), ethylene oxide, ethylene glycol, vinyl chloride, and more.

Plant Growth Regulators: Ethylene-based products are used as plant growth regulators in agriculture and horticulture. They can be employed to control fruit ripening, promote flowering, inhibit sprouting, and regulate plant height.

Welding: Ethylene gas can be used as a fuel gas in oxyfuel welding and cutting processes, although it is less common than acetylene.

Safety Considerations: Ethylene gas is flammable and should be handled with caution. Here are some safety considerations:

Storage and Handling: Ethylene gas should be stored in appropriate containers or cylinders designed for flammable gases. It should be handled in well-ventilated areas, away from ignition sources and heat.

Fire Hazards: Ethylene is highly flammable and can form explosive mixtures with air. Proper precautions should be taken to prevent the accumulation of flammable concentrations and to minimize the risk of ignition.

Toxicity: Ethylene gas itself is not highly toxic. However, it can displace oxygen in confined spaces, leading to an oxygen-deficient environment.

Proper ventilation is essential when working with ethylene gas.

When using ethylene gas in industrial or agricultural applications, it is important to follow all recommended safety guidelines, regulations, and best practices to ensure safe handling, storage, and use.

Please note that the specific regulations and safety requirements for handling ethylene gas may vary depending on the jurisdiction and the intended use/application.

Basic Info.

Model No:	C2H4	Transport Package	Cylinder
Specification:	40L	Trademark	CMC
Origin:	Suzhou	HS Code	2812190091
Production Capacity:	5000 Tons Per Month		

Specification:

Product Name:	Ethene
Molecular Formula:	C ₂ H ₄
CAS No:	74-85-1
Formula weight :	28.05
EC No:	200-815-3
Grade :	Electron Grade, Industrial Grade
Purity:	99.999%
Appearance:	Colorless
Filling weight (40L):	10kg/cylinder
Valve NO.:	QF-90A CGA350
Boiling Point:	?104°C
Melting Point:	?169°C
Cylinder Type:	DOT Steel Cylinder
Cylinder Working Pressure:	150bar

Detailed Photos



Company
Profile

About us



Shanghai Kemike Chemical Co., Ltd is staffed by trained personnel, combine many years experience in Gas industry .We supply cylinder gas, electronic gas, etc ., and the gas holder, panel, valves and fittings and other equipment, parts and engineering services to our customers in China and worldwide; The products are involved in various industrial fields, such as semiconductor chip, solar cell, LED, TFT-LCD, optical fiber, glass, laser, medicine , etc.. Our mission is to partner with our global customers to provide support, solutions and quality products that are innovative, reliable, and safe. Our products mainly include: H₂, O₂, N₂, Ar, CO₂, propane, acetylene, helium, laser mixed gas, SiH₄, SiH₂Cl₂, SiHCl₃, SiCl₄, NH₃, CF₄, NF₃, SF₆, HCL, N₂O, doping mixed gas (TMB, PH₃, B₂H₆) and other electronic gases.

SiCl ₄	NH ₃	NH ₃	CH ₃ F	SiH ₄	Kr	H ₂ S	WF ₆	F ₆ +Cl ₂
4MS	C ₃ F ₈	C ₃ F ₈	TEOS	CH ₄	PH ₃	SF ₆	C ₂	HCl+Ne
CF ₄	C ₄ F ₈	SiH ₂						TMB+H ₂
SiF ₄	C ₃ H ₈	Cl ₂						He +As
BBr ₃	C ₃ H ₆	DCE						Ge+Se
POCl ₃	N ₂	SO ₂						D+B
BCl ₃	D ₂	CO ₂						CO+NO
SiHCl ₃	CH ₂ F ₂	HF						Ar+O ₂
TMAI	DMZn	DEZn						Xe+NO
			AsH ₃	C ₂ H ₄	C ₂ H ₂	HBr	COS	
			GeH ₄	C ₂ H ₆	B ₂ H ₆	H ₂ Se	GeCl ₄	



 **Shanghai Kemike Chemical Co.,Ltd**

 +86 18762990415

 williamchen@cmc-chemical.com

 gascylindertank.com