

China

CMC

COA

Bcl3

Cylinder

Cylinder Gas China High Purity 99.999% Boron Trichloride Bcl3 Gas

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1kg
- Price: US \$18
- · Packaging Details:
- Delivery Time: 15 days
- Payment Terms: L/C, T/T
- Supply Ability: 300,000tons/year



Product Specification

- Product Name:
- Valve:
- Boiling Point:
- Melting Point:
- Cylinder Pressure:
- Cylinder Standard:
- Transport Package:
- Specification:
- Trademark:
- Origin:
- HS Code:
- Supply Ability:
- CAS No.:
- Formula:
- EINECS:

More Images

-191.5ºC -205ºC 12.5MPa/15MPa/20MPa GB/ISO/DOT 40L/47L/50L 40L/47L/50L CMC

Boron Trichloride

Qf-30A/Cga350

- China
- 2812191090
- 300, 000tons/Year
- 10294-34-5
- Bcl3
 - 233-658-4











Our Product Introduction



Product Description

Boron trichloride, or BCl3, is a chemical compound composed of boron and chlorine. It is a colorless gas at room temperature and is known for its pungent odor. BCl3 is highly reactive and is used in various industrial applications.

One common use of BCl3 is as a catalyst in organic synthesis reactions. It can be used to promote reactions such as the formation of carboncarbon and carbon-nitrogen bonds. BCl3 is also used in the production of pharmaceuticals, dyes, and other organic compounds.

Another application of BCl3 is in the production of semiconductors. It is used as a dopant during the fabrication of certain types of transistors and integrated circuits. BCl3 can introduce boron atoms into the semiconductor material, altering its electrical properties.

BCl3 is also used in the manufacturing of optical fibers. It is involved in the process of vapor deposition, where layers of glass are deposited onto a substrate to form the fiber. BCl3 is used as a reactant gas to facilitate the deposition of boron-doped silica layers, which can enhance the fiber's refractive index and optical properties.

It's worth noting that BCl3 is a toxic and corrosive substance, and proper safety precautions should be taken when handling it. Inhalation or skin contact with BCl3 can be harmful, and exposure to high concentrations can cause severe respiratory and eye irritation.

Basic Info

Transport Package: Trademark:	40L/47L/50L CMC	Melting Point Boiling Point	-107.3ºC 12.5ºC
Specification	99.90%	Production Capacity	300, 000tons/Year
Cylinder Pressure	e 12.5MPa/15MPa/20MPa	Valve	Cga660
Appearance	Colorless Fuming Liquid or Gas with a Pungent	Density	1.35 Kg/M

Specification:

Dot Class: 2.3 State: Liquid Purity: 99.9% UN NO:UN1741 CAS NO: 10294-34-5 Grade Standard: Industrial Grade

Specification99.9%Chlorine≤ 10 ppmSilicon Tetrachloride≤ 300 ppm

Packaging & Shipping

Cylinder SpecificationsContentsCylinder CapacityValveWeight47LCGA 66050 kgs

Detailed Photos



Company

Profile



