China

CMC

COA

Wf6

Cylinder/Tank

Tungsten Hexafluoride

Tungsten Hexafluoride

Sea Transportation

10L 40L 50L

2812190091

200t/Year

7783-82-6

232-029-1

Industrial Pure Air

Wf6

Colorless 99.999%

By Sea

CMC

China

# Semiconductor Industry Application Wf6 Gas Tungsten Hexafluoride

#### **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 Piece
- Price: US \$ 15/PC
- Packaging Details:
- Delivery Time: 15 days
- Payment Terms: L/C, T/T
- Supply Ability: 200 Tons/Year



## **Product Specification**

- Product Name:
- Appearance:
- Purity:
- Transport:
- Model No.:
- Transport Package:
- Specification:
- Trademark:
- Origin:
- HS Code:
- Supply Ability:
- CAS No.:
- Formula:
- EINECS:
- Constituent:





## More Images



### **Product Description**

Tungsten hexafluoride (WF6) is a chemical compound composed of tungsten and fluorine atoms. It is a colorless gas at room temperature and is primarily used in the semiconductor industry for the chemical vapor deposition (CVD) process to deposit thin films of tungsten. Here are a few key points about tungsten hexafluoride gas:

Chemical Formula: WF6

Physical Properties: Tungsten hexafluoride is a dense gas with a density of 13.1 g/cm<sup>3</sup>. It has a boiling point of 17.1 °C (62.8 °F) and can exist as a gas at room temperature and atmospheric pressure.

Reactivity: WF6 is highly reactive and can readily react with water vapor in the air to form tungsten oxide and hydrofluoric acid. It is also corrosive to many materials, including metals, glass, and ceramics.

Uses: The main application of tungsten hexafluoride is in the semiconductor industry. It is used as a precursor for depositing thin films of tungsten in the fabrication of microelectronic devices. WF6 is also used in the production of tungsten metal and as a reagent in various chemical reactions. Safety Considerations: Tungsten hexafluoride is a toxic and corrosive substance. It can cause severe burns and eye damage upon contact. Inhalation of the gas can result in respiratory irritation and other health hazards. Proper safety precautions, such as handling it in a well-ventilated area and using appropriate personal protective equipment, are essential when working with WF6.

#### Overview

Basic Info.			
Model NO.	WF6	Transport Package	Cylinder
Specification	10L/15kg	Trademark	CMC
Origin	Suzhou, China	HS Code	2812190091
Production Capacity	200t/Year		

Product Description

#### Product Spec:

ungsten Hexafluoride WF6 GAS CAS No.: 7783-82-6 EINECS No.: 232-029-1 UN No.: UN2196 Purity: 99.999% Dot Class: 2.3 Appearance: Colorless Grade Standard: Electron Grade,Industrial Grade

#### The COA of Product:

Test items	Unit	s Quality requirement	s Test results
CF4	ppm	<0.5	<0.01
02	ppm	<0.5	<0.01
N2	ppm	<1	0.03
со	ppm	<0.5	<0.02
CO2	ppm	<0.5	<0.01
SiF4	ppm	<0.5	<0.1
SF6	ppm	<0.5	<0.1
HF	ppm	<5	0.19
AI	ppb	≤10	<0.020
As	ppb	≤10	<0.001
В	ppb	≤10	<0.005
Са	ppb	≤5	<0.200
Cd	ppb	≤2	<0.001
Cr	ppb	≤10	<0.020
Fe	ppb	≤10	<0.007
К	ppb	≤5	<0.100
Mn	ppb	≤10	<0.001
Na	ppb	≤5	<0.040
Th	ppb	≤0.1	<0.001
Ті	ppb	≤10	<0.002
Li	ppb	≤10	<0.002
U	ppb	≤0.05	<0.001
Zn	ppb	≤10	<0.005
Si	ppb	≤10	<0.100
Pb	ppb	≤10	<0.001
Р	ppb	≤2	<0.300

Mg ppb	≤10	<0.020
Ni ppb	≤20	<0.030
Cu ppb	≤5	<0.005
Mo ppb	≤10	<0.001
Total impurities of other metal ppb	≤500	<0.0010

Detailed Photos





Shanghai Kemike Chemical Co., Ltd is staffed by trained personnel, combine many years experience in Gas industry .We supply cylinder gas, electronic gas, etc., and the gas holder, panel, valves and fittings and other equipment, parts and engineering services to our customers in China and worldwide; The products are involved in various industrial fields, such as semiconductor chip, solar cell, LED, TFT-LCD, optical fiber, glass, laser, medicine, etc., Our mission is to partner with our global customers to provide support, solutions and quality products that are innovative, reliable, and safe. Our products mainly include: H2, O2, N2, Ar, CO2, propane, acetylene, helium, laser mixed gas, SiH4, Sih2cl2, SiHCL3, SiCL4, NH3, CF4, NF3, SF6, HCL, N2O, doping mixed gas (TMB, PH3, B2H6) and other electronic gases.

